

## Brick & Stone Cleaner

Item 83-6, 83Q

- Concentrated masonry cleaner
- Penetrates and emulsifies soot, smoke and creosote
- Professional strength



### Description:

A professional cleaner designed to penetrate and remove combustion residues such as smoke, soot and creosote.

### Performance Characteristics:

- Contains no dangerous acids
- Industrial-strength solvent

### Recommended Uses:

To clean smoke, soot and creosote from brick and stone surfaces. For use on marble or granite, dampen area then test in an unseen area first.

### Surface Prep:

To assure compatibility, we recommend testing Brick & Stone Cleaner on a small unseen area before treating larger surfaces. Area to be cleaned should be at room temperature. Dampen area to be treated with water.

### Application:

Liberally spray dampened area with Brick & Stone Cleaner. Clean off any overspray on metal and glass right away. Will not harm metal and glass, but it will be difficult to remove after drying. Scrub brick and stone vigorously with wet non-metallic brush to get deep into pores. DO NOT LET AREA DRY, until thoroughly rinsed with clean water. Remove all traces of cleaner before it dries. Repeat the process if necessary. If using outdoors, use care to protect area vegetation. For persistent dark stains, use peroxide mixed with small amount of white vinegar as a cleaning agent.

### Clean up:

Clean up with water. If overspray is allowed to dry on glass, use Rutland's item 84 or 565 to remove residue.

### Typical Physical Properties:

|                  |  |
|------------------|--|
| Solvent          | Water, dipropylene glycol methyl ether |
| Weight/Gallon    | 8.3                                    |
| Consistency      | Liquid                                 |
| Flashpoint       | N/A                                    |
| Color            | Clear                                  |
| Storage/Handling | Store right side up and Rotate stock   |

### Limitations:

Will not bring original pristine color back to blackened fireboxes.

### Warranty and Limited Remedy:

This product will be free from defects in material and manufacture for a period of eighteen (18) months from date of manufacture. Rutland Fire Clay Company makes no other warranties including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose. User is responsible for determining whether the Rutland Fire Clay Company product is fit for a particular purpose and suitable for user's application. If this Rutland Fire Clay Company product is defective within the warranty period stated above, your exclusive remedy and Rutland Fire Clay Company's sole obligation shall be, at Rutland Fire Clay Company's option, to replace the

Rutland Fire Clay Company product or refund the purchase price of the Rutland Fire Clay Company product.

**Limitation of Liability:**

Except where prohibited by law, Rutland Fire Clay Company will not be liable for any loss or damage arising from this Rutland Fire Clay Company product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

**CAUTIONS:**

**Product is alkaline. Avoid contact with eyes and skin. Wear rubber gloves while handling. In case of eye contact, flush with plenty of water for at least 15 minutes, and consult a physician immediately. Wash hands with water. Do not inhale or ingest. May irritate nose and throat. May cause gastrointestinal irritation. If ingested, consult a physician.**

**KEEP OUT OF REACH OF CHILDREN  
EYE AND SKIN IRRITANT**