



Technical Data Sheet

Installation of the HearthStone Mantle Shield

Kit# 94-79700

Date: 6/16/2004

Page: 1 of 2

KIT CONTENTS:


- 1 – Mantle Shield
- 4 – Ceramic Spacers
- 4 – #10 x 1½” Screws

TOOLS REQUIRED:

- Philips screwdriver
- Drill
- ½” drill bit
- Tin snips or offset shears
- Tape measure

PROCEDURE:

1. Measure the distance between the uprights of your mantle. If this measurement is more than 48” proceed to step #4.
2. Subtract this measurement from 48 1/8” and divide the result by two. Measure in this distance from both ends of the Mantle Shield and make marks. Thus marking the Mantle Shield length about its center.
3. Using tin snips or offset shears, cut both ends of the mantle shield on the marks made in step #2.
4. Center the Mantle Shield under the mantle in the orientation shown below. There should be approximately 1/16” between the Mantle Shield and each upright.



5. If the Mantel Shield protrudes further into the room than desired, the back of the Mantel Shield may be trimmed. There are several mounting holes to accommodate for different depth mantles.
6. With the Mantel Shield against the wall, mark a hole toward the wall on one side, leaving enough space from the wall to drill the hole.
7. Using the 1/8" drill bit, drill a hole on the mark approximately 1/2" deep.
8. Insert a Screw through the Mantel Shield, through a Ceramic Spacer, and into the hole. Tighten the screw.
9. Drill three more holes near each corner of the mantle using the existing holes in the Mantel Shield as guides. Be sure the front two holes are at least 1/2" from the front of the mantle
10. Assemble the remaining parts as described in Step #8.