

Valcourt

GENERAL FEATURES

Combustion technology	Non-catalytic
Fuel type	Dry cordwood (16" recommended)
Recommended heating area-ft ²	<1,000
Overall firebox volume-ft ³	6.4
Burn rate	>5 kg/h (>11 lb/h)
High-efficiency certified appliance	Exempt
Maximum log length	30"
Log positioning	Loading over width
Chimney diameter	8"
Flue outlet diameter	8"
Type of chimney	CAN/ULC S629, UL 103 HT (2100 °F)
Minimum chimney height (feet)	15'

Approved for a mobile home installation	No
Shipping Weight	765 lb (347 lb)
Door type	Guillotine, glass with steel frame
Glass type	Ceramic glass
Glass surface – dimensions (Width X Height)	41 1/8" X 14 7/8"
Overall dimension (Height)	63 3/4"
Overall dimension (Width)	63 1/8"
Overall dimension (Depth)	31 3/4"
Door opening – dimension (Height)	15 1/2"
Door opening - dimension (Width)	44 1/2"
Firebox – dimension (Height)	23 1/4"
Firebox – dimension (Width)	31 7/8"
Firebox – dimension (Depth)	10 3/4"
Moulded refractory bricks	Yes
Cast iron andirons	Yes
USA standard (safety)	UL 127
Canadian standard (safety)	ULC-S610
Tested and listed as per applicable standards	By an accredited laboratory (CAN/USA)
Warranty	Limited lifetime

APPROVED CHIMNEY TYPES

Manufacturers*	Brand	Type	Diameter
American Metal	HSS	AC Triple Wall	8" (20 cm)
American Metal	HS	AC Triple Wall	8" (20 cm)
DuraVent	DuraTech Premium	2" Solid Pack	8" (20 cm)
DuraVent	DuraPlus HTC	2" Solid Pack	8" (20 cm)
DuraVent	DuraPlus	AC Triple Wall	8" (20 cm)
Metal Fab	Temp Guard	1" Solid Pack	8" (20 cm)
Olympia Chimney	Champion Chimney System	1" Solid Pack	8" (20 cm)
Olympia Chimney / SBI Division Venting	Ventis	1" Solid Pack	8" (20 cm)
SBI Venting Division	Nexvent	1" Solid Pack	8" (20 cm)
Security Chimney	S-2100 +	2" Solid Pack	8" (20 cm)
Selkirk	CF Sentinel (CF)	2" Solid Pack	8" (20 cm)
Selkirk	Super Pro 2100 (ALT)	2" Solid Pack	8" (20 cm)
Selkirk	Super Vent 2100 (JM)	2" Solid Pack	8" (20 cm)

* Specific components may be required depending on the chimney manufacturer.

Minimum clearances to combustibles*

(Data expressed in inches. 1 inch = 25.4 mm)

	Canada	United-States
Clearance – top (measured from the platform on which the appliance is installed)**	84"	84"
Clearance – combustible side mantle to unit	8 1/2"	8 1/2"
Clearance – combustible top mantle to unit	64 3/4"	64 3/4"
Clearance – combustible side wall to unit	24"	24"
Clearance - from the shelf to the base of the fireplace	48"	48"

* The information given on the certification label affixed to the appliance always overrides the information published in any other media (owner's manual, catalogues, flyers, magazines and/or web sites).

** Some appliances have been tested with a low ceiling. Before setting up your unit, refer to the installation manual.
