

# ST. CROIX MULTI-FUEL INSERT AND STOVE SPECIFICATIONS

ASHBY-MF



ECLIPSE-MF



GREENFIELD



AUBURN



LANCASTER



	ASHBY-MF	ECLIPSE-MF	GREENFIELD	AUBURN	LANCASTER
Width	45" (with std. surround)	25"	25"	24 ¾"	20"
Height	32" (with surround)	31"	32 ½"	34"	28 ½" (37 ¾" with legs)
Depth	24"	23"	23 ½"	26"	18"
Vent Size	3" rear vent	4" rear vent	3" rear vent	3" rear vent	3" rear vent
Minimum Fireplace Opening (Width)	24"	—	—	—	—
Minimum Fireplace Opening (Height)	20 ¾"	—	—	—	—
Minimum Fireplace Opening (Depth)	16"	—	—	—	—
Heating Capacity <sup>1</sup>	up to 1,800 sq. ft.	up to 2,100 sq. ft.	up to 1,800 sq. ft.	up to 1,800 sq. ft.	up to 1,800 sq. ft.
Hopper Capacity <sup>2</sup>	60 lbs.	85 lbs.	50 lbs.	90 lbs.	35 lbs. (70 lbs. optional)
Burn Rate <sup>4</sup> (lbs./hr.)	1.25-4.5	1.7-6.0	1.25-4.5	1.25-4.5	1.25-4.5
BTUH <sup>4</sup>	Up to 40,000	Up to 50,000	Up to 40,000	Up to 40,000	Up to 40,000
Ash Drawer	Yes	Yes	Yes	Yes	Yes
Electronic Ignition	No	Yes	No	No	No
Digital Controls	Yes	Yes	Yes	Yes	Yes
Room Thermostat	Optional	Optional	Optional	Optional	Optional
Shipping Weight	267 lbs.	385 lbs.	427 lbs.	285 lbs.	240 lbs.

<sup>1</sup>Heating capacity will vary with home construction and climate.

<sup>2</sup>Hopper capacities will vary depending on the weight and volume of the fuel.

<sup>3</sup>The Eclipse-MF has two hoppers—the standard 65 lb. hopper and a smaller 20 lb. hopper that feeds into the electronic ignition.

<sup>4</sup>Burn rate and BTUH will vary with fuel.

Safety test statement tested per: ASTM/E1509 UL1482,

CAN/ULC 5627 B 366.2M/APFI/ASTM/E1509

Oregon Administrative Rules: 814-23-900 thru 814-23-909

Power requirements: 120 Volts AC (200-250 watts)



Products, specifications and prices subject to change without notice. Consult our Owner's Manuals for all final dimensions. St. Croix products are manufactured in the U.S.A.